



MAGNA™ GLOBEUS XHD-XTRA

MAGNA™ GLOBEUS XHD-XTRA— Premium quality versatile monograde diesel engine oil manufactured from high quality base oil and advanced chemical additives for use in mixed fleet operations.

Applications

MAGNA GLOBEUS XHD XTRA Used as engine oil in turbo-charged and naturally aspirated diesel and gasoline engines. They also meet the transmission oil requirement for some off-road, construction and military equipment. Specially formulated to protect engines from extreme wear, deposit and sludge formations.

Specifications: Meets

API CF

- ACEA E1-96
- MB 227.0
- ALLISON C-3
- CATERPILLAR TO-2
- MAN 270

Features & Benefits

- Excellent high thermal stability and resistance to oxidation.
- Controls low temperature sludge formation.
- Ensures engine and cam cleanliness.
- Excellent resistance to corrosion and rust.
- Limits engine and transmission wear.

Typical Characteristics

GLOBEUS XHD - XTRA SAE	10W	30	40	50
API Grades	CF	CF	CF	CF
Density @ 15°C Kg/m ³	878	895	900	905
Kinematic viscosity, 40°C cSt	46	106	158	238
Kinematic viscosity, 100°C cSt	7.2	12.3	15.5	19.1
Viscosity Index	115	104	106	102
Flash point, COC, °C	210	214	220	238
Pour point, °C, Max	-33	-21	-15	-11
TBN – mgKOH/g	10	10	10	10
Sulphated Ash, %wt	1.3	1.3	1.3	1.3

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.