



MAGNA™ GLOBEUS - XTREME

MAGNA™ GLOBEUS - XTREME– Heavy duty diesel engine oil to meet the requirements of vehicle running on high Sulphur fuel.

Applications

MAGNA GLOBEUS EXTREME Specially formulated with high quality base stock and special chemical additives for use in all naturally aspirated and turbo charged diesel engines running on high Sulphur diesel fuels.

Specifications: Meets

API CD

- MIL-L-2104D
- DEF-2101 D
- CAT-SERIES 3

Features & Benefits

- High TBN lubricants protect the engine against corrosion and wear when using 1.0% and above mass Sulphur diesel fuel.
- Provides excellent engine cleanliness.
- Reduces engine wear.
- Provides good thermal stability.
- Protects against oxidation, rust and corrosion.

Typical Characteristics

GLOBEUS XTREME SAE	30	40
API Grades	CD	CD
Density @ 15°C Kg/m ³	895	900
Kinematic viscosity, 40°C cSt	106	156
Kinematic viscosity, 100°C cSt	12.3	15.2
Viscosity Index	107	106
Flash point, COC, °C	218	225
Pour point, °C, Max	-18	-13
TBN – mgKOH/g	20	20
Sulphated Ash, %wt	2	2

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.