



MAGNA TM SYNERGY 4T

MAGNA TM SYNERGY 4T – a premium quality, synthetic engine oil designed primarily for use in 4-stroke cycle motorcycles, scooters, and all-terrain vehicles (ATVs). It also may be used as transmission oil in motorcycles and ATVs where the manufacturer specifies the use of motor oil in the transmission. 4T Synthetic MA is formulated to provide excellent wear protection, to minimize the formation of sludge and varnish, and to resist viscosity and thermal breakdown at high temperatures. It also protects against rust and bearing corrosion and is resistant to excessive foam buildup and air entrainment. The synthetic formulation provides additional thermal stability at high temperatures. 4T Synthetic MA meets the performance requirements of major motorcycle manufacturers and API Service SL. It meets JASO MA friction test requirements for use in motorcycle engines with integrated clutch and transmission.

Applications

4-stroke cycle motorcycles, scooters, and ATVs

- 4-stroke cycle gasoline engines in other mobile or stationary equipment where an API Service SL quality oil is specified 4T Synthetic MA meets or exceeds the requirements of and is approved for:
- JASO T 903:2011 Performance Classification MA

Features & Benefits

- Enhanced resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against scuffing and wear
- High shear stability
- Protects against rust and bearing corrosion
- Good resistance to foaming and air entrainment
- Proper frictional properties to avoid clutch slippage

Specifications: Meets

API SL

- JASO MA
- JASO MA2

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.



Typical Characteristics

MAGNA SYNERGY 4T	10W-40	10W-50
API Grade	SL	SL
Specific Gravity @ 60°F	0.857	0.868
Density, lbs/gal @ 60°F	7.14	7.56
Color, ASTM D1500	2.5	2.5
Flash Point (COC), °C (°F)	234 (453)	234 (453)
Pour Point, °C (°F)	-46 (-51)	-46 (-51)
Viscosity, Kinematic		
cSt @ 40°C	102	138.1
cSt @ 100°C	15	19.5
Viscosity Index	154	156
Cold Cranking Viscosity, cP	6184	6300
@ (°C)	(-25)	(-20)
High Temp/High Shear Viscosity, cP @ 150°C	4.2	5
Sulfated Ash, ASTM D874, wt %	0.98	0.98
Total Base Number (TBN), ASTM D2896	7.7	7.8
Phosphorus, wt %	0.114	0.114
Zinc, wt %	0.125	0.125

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.