



MAGNA™ SYNERGY OUTBOARD MOTOR OIL

MAGNA™ SYNERGY OUTBOARD MOTOR OIL– High performance two stroke outboard motor oil for use in high power water and air cooled engines.

Applications

MAGNA SYNERGY OUTBOARD MOTOR OIL Blended from high quality base oils and special additives which keeps spark plugs, pistons clean of carbon deposits. It can be mixed with leaded and unleaded gasoline in self-mixing or oil injections systems.

Special note: Always follow manufacturer recommended oil-fuel ratio for better performance.

Specifications: Meets

- NMMA TC-W3
- SAE J 1536/ FLUIDITY GRADE 3

Features & Benefits

- Excellent protection against corrosion and wear.
- Gives excellent protection against deposits.
- Protection against spark plug fouling and pre-ignition.
- Miscible with all gasoline around the year.
- Reduce exhaust emissions.

Typical Characteristics

Density @ 15°C Kg/m³	866
Kinematic viscosity, 40°C cSt	42
Kinematic viscosity, 100°C cSt	7.1
Viscosity Index	121
Flash point, COC, °C	83
Pour point, °C, Max	-38
TBN – mgKOH/g	4.5
Sulphated Ash, %wt	<0.02

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.