



MAGNA™ SYNERGY PREMIUM

MAGNA™ SYNERGY PREMIUM– High performance engine oil designed for use in all passenger cars equipped with gasoline, diesel engines and turbo charged units.

Applications

MAGNA SYNERGY PREMIUM is blended and manufactured from highly refined base stock incorporating advanced additives which gives unsurpassed conventional protection to automobiles equipped with gasoline, diesel engine and turbo charged units of all major manufacturer.

Specification

API- SL

- ACEA A3/B3
- MB 229.1
- VW 501.01,500.00
- ILSAC GF-4
- Recommended for all Jap, Korean & Chinese OEM

Features & Benefits

- Excellent oil film strength and high oxidation and thermal stability.
- Excellent protection for all driving conditions.
- Premium additives to prevent wear.
- Prevents piston deposits and the formation of black sludge.

Typical Characteristics

SYNERGY PREMIUM	SAE	20W50
API Grades		SL
Density @ 15°C Kg/m ³		891
Kinematic viscosity, 40°C cSt		178
Kinematic viscosity, 100°C cSt		19.4
Viscosity Index		127
Flash point, COC, °C		230
Pour point, °C, Max		-30
TBN – mgKOH/g		9.5

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.