



MAGNA TM SYNERGY SUPER-2000

MAGNA TM SYNERGY SUPER-2000— High quality monograde engine oil suitable for use in all major passenger cars.

Applications

MAGNA SYNERGY SUPER-2000 Premium quality monograde motor oil manufactured from high quality base stock and high-quality additives which offers very good oxidation stability, antiwar performance and protection against engine deposits, rust, and corrosion.

Specifications: Meets

API SG

- MIL-L-46152 D
- FORD ESE M2C153-E
- GM 6094M

Features & Benefits

- Economy grade for moderate operating conditions.
- Provide good lubrication.
- Keeps engine clean by special additives.
- Excellent protection against oxidation and thermal breakdown.
- Low maintenance cost through better oil performance.

Typical Characteristics

SYNERGY SUPER – 2000 SAE	10W	30	40	50
API Grades	SG	SG	SG	SG
Density @ 15°C Kg/m ³	876	888	889	901
Kinematic viscosity, 40°C cSt	43.7	103	155	223
Kinematic viscosity, 100°C cSt	7.3	11.6	14.9	19
Viscosity Index	119	105	105	97
Flash point, COC, °C	210	214	218	230
Pour point, °C, Max	-28	-21	-18	-12
TBN – mgKOH/g	8	8	8	8

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.