



MAGNA™ SYNERGY SUPREME

MAGNA™ SYNERGY SUPREME– High quality advance mineral lubricants for all modern passenger car engine.

Applications

Blended and manufactured from highly refined base stock together with selective advanced special additives to give an excellent level of protection for all passenger cars of all major car manufacturers.

Specification: Meets

API SJ

- ACEA A3/B3
- MB 229.1
- VW 501.01.505.00
- BMW LONG LIFE

Features & Benefits

- Excellent protection against cylinder and cam wear.
- Provides excellent protection at cold start and at high temperatures.
- Extends drainage intervals and reduces maintenance costs.
- Excellent sludge and deposit formation control.
- Prohibits corrosion and protects against rust.

Typical Characteristics

SYNERGY SUPREME -SAE	15W50	20W50
API Grades	SJ	SJ
Density @ 15°C Kg/m ³	889	891
Kinematic viscosity, 40°C cSt	145	173
Kinematic viscosity, 100°C cSt	19	19.4
Viscosity Index	145	127
Flash point, COC, °C	230	220
Pour point, °C, Max	-30	-27
TBN – mgKOH/g	9.2	9.2
Sulphated Ash, %wt	1.2	-

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.