



MAGNA™ ADHESIVE OIL

MAGNA™ ADHESIVE OIL— Premium quality residual compound lubricants with natural inherent strength against washout and blended with special additives to prevent rust and promote metal wetting and penetration.

Applications

MAGNA ADHESIVE OIL Expressly recommended for use where heavy adhesive oil is required, like open gears, chains, sprockets and wire ropes of drag lines, shovels, and dredging equipment where resistance to water wash out and penetration of wire ropes is a consideration.

AVAILABILITY: Light tacky and heavy tacky

Features & Benefits

- Forms a durable, adhesive coating that will not be thrown or wiped from the ropes as it operates over pulleys and drums.
- Excellent metal wetting and penetration of wire ropes preventing.
- Rope core from drying out and deteriorations.
- Resists water washout.
- Protects against rusting and corrosion by acid, alkane or salt after.
- Excellent metal adhesive properties.

Typical Characteristics

ADHESIVE OIL		
Appearance	Light tacky oil	Heavy tacky oil
Kinematic viscosity, 40°C cSt	1200	9000
Kinematic viscosity, 100°C cSt	100	1100
Flash point, COC, °C	270	270
Pour point, °C, max	0	10

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.